

XG1212DC/XG1412DC

SCISSOR LIFTS


FEATURES

PRODUCTIVITY

- 2 front driving wheels
- 25% theoretical gradeability-stowed/lowered position
- Battery charge indicator and diagnostic display
- Manual platform lowering valve
- Both platform and ground control panel with emergency stop button
- Front wheel multi-disc brakes
- Manual brake release system
- Solid non-marking tires
- Mobile pothole protection
- Tilt alarm
- Hourmeter screen
- Lift and lower alarm
- Horn
- Dual flashing beacons
- Drive alarm
- Overload alarm

OPTIONS

- Platform working light
- Air-line to platform
- AC power to the platform
- AC motor
- Li-battery



Item	Unit	XG1212DC	XG1412DC
Lift capacity	kg	320	320
Lift capacity of extended platform	kg	115	115
Occupant Capacity	-	2	2
Working height	m	12	13.8
Platform height	m	10	11.8
Extended platform size(Length x Width)	mm	900	900
Ground clearance(pil protector rising/descending)	mm	100/20	100/20
Turning radius(inner/outer wheel)	m	0/2.3	0/2.3
Drive motor	kW	0.75	0.75
Lift motor	kW	4.5	4.5
Drive speed at low level	km/h	4.0	4.0
Drive speed at high level	km/h	0.8	0.8
Lift/Lower time	s	50~75/43~65	45~70/52~78
Gradeability	%	25	25
Tilt alarm(side/forward and backward)	°	1.5/3	1.5/3
Batteries	V/Ah	4 x 6/280	4 x 12/240
Charger	V/A	24/30	24/30
Tires	-	381 x 127	381 x 127
Weight	kg	2900	3100
a Length(without ladder)	mm	2477(2267)	2477(2267)
b Width	mm	1170	1190
c Height(platform folded)	mm	2480(1930)	2610(2060)
d x e Platform size(Length x Width)	mm	2277 x 1120	2277 x 1120
f Wheelbase	mm	1877	1877